


Magnesium

3

CABLE SUSPENDED (CS)



PREMIUM LEDS WITH VARIOUS COLOR TEMPERATURES AND LIGHT OUTPUT
HIGH EFFICACY REFLECTORS
MACHINED END CAPS
EXTRUDED ALUMINUM HOUSING
SOFT GLOW FROSTED LENS

FEATURES:

- Powered Suspension System - No power cord
- High transmission frosted lenses with no diode imaging
- No visible fasteners
- Extruded aluminum housing
- Dimmable/Programmable drivers for controllable light output
- High efficacy LEDs with 5 year warranty
- Under 2 steps MacAdams Ellipse Binning
- 5/8" thick machined end caps
- Bi-directional fixture
- 360 rotation option- with mechanical locking
- Slightly recessed beveled lens housing

NOTES:

REQUIRES REMOTE DRIVER(S) (see page 3 for more)



PRODUCT SPECIFICATION

NOTE: All options *italicized in gray* may increase lead times and/or incur higher costs - please consult factory with questions.

FIXTURE TYPE	MOUNTING/ ORIENTATION	NOMINAL LENGTH*	COLOR TEMP	LED DRIVE POWER		VOLTAGE	DRIVER	HOUSING FINISH
				LARGE APERTURE	SMALL APERTURE*			
Mg3 Magnesium 3								
	CSD Cable Suspended - DIRECT ONLY	1' 1-5/8"*** 2' 2-1/5/8"***	27K 2700K 30K 3000K	VLO Very Low Output 435 lumens/ft. (4w/ft.)	VLO Very Low Output 405 lumens/ft. (4w/ft.)	UNV Universal (120-277v)	ND Non-Dimming 0-10v DIMMING	SC Satin Clear Anodize (Standard)
	CSLAD Cable Suspended - LARGE APERTURE DIRECT	3' 3-1-5/8"*** 4' 4-1-5/8"***	35K 3500K 40K 4000K	LO Low Output 660 lumens/ft. (6w/ft.)	LO Low Output 615 lumens/ft. (6w/ft.)	1V 120v 2V 227v 3V 347v*	10D 10% DIM 1D 1% DIM LUTRON	SW Satin White (Powder Coat)
	CSLAI Cable Suspended - LARGE APERTURE INDIRECT	5' 5-1-5/8"*** 6' 6-1-5/8"*** 7' 7-1-5/8"*** 8' 8-1-5/8"***	50K 5000K	SO Standard Output 865 lumens/ft. (8w/ft.)	SO Standard Output 805 lumens/ft. (8w/ft.)		LTEA Lutron Hi-Lume 1% (2-Wire) LDE1 Lutron EcoSystem 1% "Soft on" (Digital) LDES Lutron EcoSystem 5% 5-Series (Digital) DALI	MB Matte Black (Powder Coat)
	CSR Cable Suspended - Rotational	CR Continuous Run (Specify length in nominal ft.)		HO High Output 1,080 lumens/ft. (10w/ft.) VHO Very High Output 1,260 lumens/ft. (12w/ft.) CPO Custom Power Output Consult factory	HO High Output 1,005 lumens/ft. (10w/ft.) VHO Very High Output 1,170 lumens/ft. (12w/ft.) CPO Custom Power Output Consult factory		DALI Digital Addressable Lighting Interface	CF Custom Finish* (Consult)
		*CR not compatible with CSLAI mounting option. *Dimensions are for reference only. Contact factory for more specific information or shop drawings.						
					*Not Applicable with CSD option.	*Not all dimming options are available with 347v.		*RAL and color match are available.

HARDWARE* DETAIL FINISH	DRIVER HOUSING FINISH	CANOPY SIZE OPTIONS*	CANOPY FINISH	POWER CORD COLOR	AIRCRAFT CABLE LENGTH*	OPTIONS/ CUSTOMIZATION*
MC Machine Finish (Standard) CF Custom Finish (Consult Factory)	MA Mill Aluminum* SC Satin Clear SW Satin White SB Satin Black CF Custom Finish (Consult Factory)	5 SERIES CANOPY 55 5" Power feed canopy 5" Non-power feed canopy 52 5" Power feed canopy 2" Non-power feed canopy 50 5" Power feed canopy Canopy only at power feed 44 4" Power feed canopy 4" Non-power feed canopy 41 4" Power feed canopy 1" Non-power feed canopy 40 4" Power feed canopy Canopy only at power feed *CONTINUOUS RUNS REQUIRE THE 55" OR THE 44" OPTION. CONSULT FACTORY WITH QUESTIONS. *See options section and installation instructions for more information.	SW Satin White (Standard) CPC Custom Powder Coat Canopy Finish* 4 SERIES CANOPY MF Machine Finish (Standard) SW Satin White CF Custom Finish*	PSS Power Suspension System (No Power Cord) CC Custom Cord*	2 2' 4 4' 6 6' 8 8' CL Custom Length** (Specify in ft. IE: CL10 for 10')	XX No EMB or Customization EMB7 7 Watt battery back-up** (Approximately 600 lumens) EMB12 12 Watt battery back-up** (Approximately 1,000 lumens) 90 90+ CRI LED BOARDS (2700K - 4000K only) CCP Corners/patterns* CD Custom Driver* CR Customization Requested*
NOTE: MF option is strongly recommended. Other options will result in higher costs and potentially longer lead times. **Hardware refers to the corners.	*Most cost effective.		*Consult the factory.		*Cables are field adjustable. ** Consult factory to confirm specific length.	NOTE: Customization may incur higher costs and/or increased lead times. *Consult the factory for all custom options or custom concept requests. **The EMB12 is slightly more expensive than the EMB7 option (BOTH OPTIONS ARE REMOTE ONLY).

SPECIFICATION INFORMATION

GENERAL NOTES:

All fixtures are **UL listed** for **dry** and **damp** locations.

REMOTE DRIVER for all options.

Please contact the factory with any specification questions.

Italicized grayed out options may incur additional costs and/or extended lead times. Please consult the factory.

FIXTURE ORIENTATION:

Direct (CSD) for downlight applications

Indirect (CSI) for uplight applications

Inward (CSIW) for sidelight applications facing the inside of the fixture

Outward (CSOW) for sidelight applications facing out

DRIVER: [REMOTE]

1) NON-DIMMING: As described... this fixture will not dim.

2) DIMMING: 0-10v: 1%, 10% :: Lutron: 2-wire Forward phase (Hi-Lume 1%, Ecosystem to 1% (Soft On), Ecosystem to 5% (5 Series).

"DALI" - Specify driver. See "Dimming Options" on subsequent pages for more information. For other dimming options, consult the factory.

3) EMERGENCY: Specify EMB under the Options/Customization category at the end of the cut sheet along with the desired lumen output (600 or 1,000 lumens - the latter is slightly more costly).

4) Drivers are programmed according to our standard lumen packages or to custom watt/lumen package requirements.

5) Consult factory with any questions or specification requirements.

FINISHES:

The standard finish is a Satin Clear anodized housing with Machine Finished hardware. Machined finish is preferable for machined components (Hardware Detail) - Powder coating these parts may result in additional costs. Consult the factory with any questions about standard or custom finishing options.

CUSTOMIZATION:

We have numerous custom options available. However, if there is something unique required for a project, from simple options to complete custom requests, we are more than willing to entertain any creative notions you might have. Just ask.



Lumium Lighting, LLC | 3590 Cadillac Ave, Suite A, Costa Mesa, CA 92626 | Phone: 760.757.2530 | Fax: 760.283.2333 | www.lumiumlighting.com

While we always strive to ensure all website content and product information is current, Lumium Lighting reserves the right to change specifications without notice. 20220917
© Lumium Lighting, LLC - All rights reserved.




Lumium
lighting at its element

Magnesium

3

ROTATIONAL ARM MOUNT (RAM)



PREMIUM LEDS WITH
VARIOUS COLOR
TEMPERATURES AND
LIGHT OUTPUT

MACHINED END CAPS
EXTRUDED
ALUMINUM HOUSING
SOFT GLOW FROSTED
LENS

FEATURES:

- 5/8" diameter rigid tube mounting system
- High transmission frosted lenses with no diode imaging
- No visible fasteners
- Extruded aluminum housing
- Dimmable/Programmable drivers for controllable light output
- High efficacy LEDs with 5 year warranty
- Under 2 steps MacAdams Ellipse Binning
- 5/8" thick machined end caps
- Bi-directional fixture
- 360 rotation option- with mechanical locking

NOTES:

REQUIRES REMOTE DRIVER(S) (see page 3 for more)




PRODUCT SPECIFICATION

NOTE: All options *italicized in gray* may increase lead times and/or incur higher costs - please consult factory with questions.

FIXTURE TYPE	MOUNTING/ ORIENTATION	NOMINAL LENGTH*	COLOR TEMP	LED DRIVE POWER		VOLTAGE	DRIVER	HOUSING FINISH*
				LARGE APERTURE	SMALL APERTURE*			
Mg3 Magnesium 3	RAM Rotational Arm Mount	1' 1'-1-5/8"*** 2' 2'-1-5/8"*** 3' 3'-1-5/8"*** 4' 4'-1-5/8"*** 5' 5'-1-5/8"*** 6' 6'-1-5/8"*** 7' 7'-1-5/8"*** 8' 8'-1-5/8"*** CR Continuous Run (Specify length in ft.)	27K 2700K 30K 3000K 35K 3500K 40K 4000K 50K 5000K	VLO Very Low Output 435 lumens/ft. (4w/ft.) LO Low Output 660 lumens/ft. (6w/ft.) SO Standard Output 865 lumens/ft. (8w/ft.) HO High Output 1,080 lumens/ft. (10w/ft.) VHO Very High Output 1,260 lumens/ft. (12w/ft.) CPO Custom Power Output Consult factory	VLO Very Low Output 405 lumens/ft. (4w/ft.) LO Low Output 615 lumens/ft. (6w/ft.) SO Standard Output 805 lumens/ft. (8w/ft.) HO High Output 1,005 lumens/ft. (10w/ft.) VHO Very High Output 1,170 lumens/ft. (12w/ft.) CPO Custom Power Output Consult factory	UNV Universal (120-277v) 1V 120v 2V 227v 3V 347v*	ND Non-Dimming 0-10v DIMMING 10D 10% DIM 1D 1% DIM LUTRON L7EA Lutron Hi-Lume 1% (2-Wire) LDE1 Lutron EcoSystem 1% "Soft on" (Digital) LDES Lutron EcoSystem 5% 5-Series (Digital) DALI DALI Digital Addressable Lighting Interface	SC Satin Clear Anodize (Standard) SW Satin White (Powder Coat) MB Matte Black (Powder Coat) CF Custom Finish (Consult Factory)
*Dimensions are for reference only. Contact factory for more specific information or shop drawings. **Odd lengths may incur slightly higher per foot pricing.				*Not Applicable with CSD option.		*Not all dimming options are available with 347v.	*RAL and color match are available.	

HARDWARE* DETAIL FINISH	DRIVER HOUSING FINISH	ARM LENGTH*	ARM LENGTH*	OPTIONS/ CUSTOMIZATION*
MF Machine Corners CF Custom Finish (Consult Factory)	MA Mill Aluminum* SC Satin Clear SW Satin White SB Satin Black CF Custom Finish (Consult Factory)	3 2' 6 4' 9 6' 12 8' 18 Custom Length** (Specify in ft. IE: CL10 for 10')	4CPF Flat 4" diameter Cover Plate - For use with a 3-O mud ring 1TR 1" Trim Ring - for use when mounting to finished surface IE. furniture NCP No Cover Plate CCP Custom Cover Plate (Consult Factory)	XX No EMB or Customization EMB7 7 Watt battery back-up** (Approximately 600 lumens) EMB12 12 Watt battery back-up** (Approximately 1,000 lumens) 90 90+ CRI LED BOARDS (2700K - 4000K only) CCP Corners/patterns* CD Custom Driver* CR Customization Requested*
NOTE: MF option is strongly recommended. Other options will result in higher costs and potentially longer lead times. **"Hardware" refers to the corners.		*Cables are field adjustable. ** Consult factory to confirm specific length.	*Cables are field adjustable. ** Consult factory to confirm specific length.	NOTE: Customization may incur higher costs and/or increased lead times. *Consult the factory for all custom options or custom concept requests. **The EMB12 is slightly more expensive than the EMB7 option (BOTH OPTIONS ARE REMOTE ONLY).



SPECIFICATION INFORMATION

GENERAL NOTES:

All fixtures are **UL listed** for **dry** and **damp** locations.

REMOTE DRIVER for all options.

Please contact the factory with any specification questions.

Italicized grayed out options may incur additional costs and/or extended lead times. Please consult the factory.

FIXTURE ORIENTATION:

Direct (CSD) for downlight applications

Indirect (CSI) for uplight applications

Inward (CSIW) for sidelight applications facing the inside of the fixture

Outward (CSOW) for sidelight applications facing out

DRIVER: [REMOTE]

1) NON-DIMMING: As described... this fixture will not dim.

2) DIMMING: 0-10v: 1%, 10% :: Lutron: 2-wire Forward phase (Hi-Lume 1%), Ecosystem to 1% (Soft On), Ecosystem to 5% (5 Series). "DALI" - Specify driver. See "Dimming Options" on subsequent pages for more information. For other dimming options, consult the factory.

3) EMERGENCY: Specify EMB under the Options/Customization category at the end of the cut sheet along with the desired lumen output (600 or 1,000 lumens - the latter is slightly more costly).

4) Drivers are programmed according to our standard lumen packages or to custom watt/lumen package requirements.

5) Consult factory with any questions or specification requirements.

FINISHES:

The standard finish is a Satin Clear anodized housing with Machine Finished hardware. Machined finish is preferable for machined components (Hardware Detail) - Powder coating these parts may result in additional costs. Consult the factory with any questions about standard or custom finishing options.

CUSTOMIZATION:

We have numerous custom options available. However, if there is something unique required for a project, from simple options to complete custom requests, we are more than willing to entertain any creative notions you might have. Just ask.



Lumium Lighting, LLC | 3590 Cadillac Ave, Suite A, Costa Mesa, CA 92626 | Phone: 760.757.2530 | Fax: 760.283.2333 | www.lumiumlighting.com

While we always strive to ensure all website content and product information is current, Lumium Lighting reserves the right to change specifications without notice. 20220917
© Lumium Lighting, LLC - All rights reserved.




Lumium
lighting at its element

Magnesium

3

SURFACE MOUNT (SM)



PREMIUM LEDs WITH
VARIOUS COLOR
TEMPERATURES AND
LIGHT OUTPUT

MACHINED END CAPS
EXTRUDED
ALUMINUM HOUSING
SOFT GLOW FROSTED
LENS

FEATURES:

- Ceiling or wall mounting system
- High transmission frosted lenses with no diode imaging
- No visible fasteners
- Extruded aluminum housing
- Dimmable/Programmable drivers for controllable light output
- High efficacy LEDs with 5 year warranty
- Under 2 steps MacAdams Ellipse Binning
- 5/8" thick machined end caps
- Bi-directional fixture
- Slightly recessed beveled lens housing

NOTES:

REQUIRES REMOTE DRIVER(S) (see page 3 for more)




PRODUCT SPECIFICATION

NOTE: All options *italicized in gray* may increase lead times and/or incur higher costs - please consult factory with questions.

FIXTURE TYPE	MOUNTING/ ORIENTATION	NOMINAL LENGTH*	COLOR TEMP	LED DRIVE POWER		VOLTAGE	DRIVER	HOUSING FINISH*
				LARGE APERTURE	SMALL APERTURE*			
Mg3 Magnesium 3	SMS Surface Mount - SIDE	1' 1'-5/8"*** 2' 2'-1-5/8" 3' 3'-1-5/8"*** 4' 4'-1-5/8" 5' 5'-1-5/8"*** 6' 6'-1-5/8" 7' 7'-1-5/8"*** 8' 8'-1-5/8" CR Continuous Run (Specify length in ft.)	27K 2700K 30K 3000K 35K 3500K 40K 4000K 50K 5000K	VLO Very Low Output 435 lumens/ft. (4w/ft.) LO Low Output 660 lumens/ft. (6w/ft.) SO Standard Output 865 lumens/ft. (8w/ft.) HO High Output 1,080 lumens/ft. (10w/ft.) VHO Very High Output 1,260 lumens/ft. (12w/ft.) CPO Custom Power Output Consult factory	VLO Very Low Output 405 lumens/ft. (4w/ft.) LO Low Output 615 lumens/ft. (6w/ft.) SO Standard Output 805 lumens/ft. (8w/ft.) HO High Output 1,005 lumens/ft. (10w/ft.) VHO Very High Output 1,170 lumens/ft. (12w/ft.) CPO Custom Power Output Consult factory	UNV Universal (120-277v) 1V 120v 2V 227v 3V 347v*	ND Non-Dimming 0-10v DIMMING 10D 10% DIM 1D 1% DIM LUTRON LITEA Lutron Hi-Lume 1% (2-Wire) LDE1 Lutron EcoSystem 1% "Soft on" (Digital) LDES Lutron EcoSystem 5% 5-Series (Digital) DALI DALI Digital Addressable Lighting Interface	SC Satin Clear Anodize (Standard) SW Satin White (Powder Coat) MB Matte Black (Powder Coat) CF Custom Finish (Consult Factory)
*Dimensions are for reference only. Contact factory for more specific information or shop drawings. **Odd lengths may incur slightly higher per foot pricing.				*Not Applicable with CSD option.		*Not all dimming options are available with 347v.	*RAL and color match are available.	

HARDWARE* DETAIL FINISH	DRIVER HOUSING FINISH	OPTIONS/ CUSTOMIZATION*
MF Machine Corners CF Custom Finish (Consult Factory)	MA Mill Aluminum* SC Satin Clear SW Satin White SB Satin Black CF Custom Finish (Consult Factory)	XX No EMB or Customization EMB7 7 Watt battery back-up** (Approximately 600 lumens) EMB12 12 Watt battery back-up** (Approximately 1,000 lumens) 90 90+ CRI LED BOARDS (2700K - 4000K only) CCP Corners/patterns* CD Custom Driver* CR Customization Requested*
NOTE: MF option is strongly recommended. Other options will result in higher costs and potentially longer lead times. **"Hardware" refers to the corners.		
NOTE: Customization may incur higher costs and/or increased lead times. *Consult the factory for all custom options or custom concept requests. **The EMB12 is slightly more expensive than the EMB7 option (BOTH OPTIONS ARE REMOTE ONLY).		



SPECIFICATION INFORMATION

GENERAL NOTES:

All fixtures are **UL listed** for **dry** and **damp** locations.

REMOTE DRIVER for all options.

Please contact the factory with any specification questions.

Italicized grayed out options may incur additional costs and/or extended lead times. Please consult the factory.

FIXTURE ORIENTATION:

Direct (CSD) for downlight applications

Indirect (CSI) for uplight applications

Inward (CSIW) for sidelight applications facing the inside of the fixture

Outward (CSOW) for sidelight applications facing out

DRIVER: [REMOTE]

1) NON-DIMMING: As described... this fixture will not dim.

2) DIMMING: 0-10v: 1%, 10% :: Lutron: 2-wire Forward phase (Hi-Lume 1%, Ecosystem to 1% (Soft On), Ecosystem to 5% (5 Series).

"DALI" - Specify driver. See "Dimming Options" on subsequent pages for more information. For other dimming options, consult the factory.

3) EMERGENCY: Specify EMB under the Options/Customization category at the end of the cut sheet along with the desired lumen output (600 or 1,000 lumens - the latter is slightly more costly).

4) Drivers are programmed according to our standard lumen packages or to custom watt/lumen package requirements.

5) Consult factory with any questions or specification requirements.

FINISHES:

The standard finish is a Satin Clear anodized housing with Machine Finished hardware. Machined finish is preferable for machined components (Hardware Detail) - Powder coating these parts may result in additional costs. Consult the factory with any questions about standard or custom finishing options.

CUSTOMIZATION:

We have numerous custom options available. However, if there is something unique required for a project, from simple options to complete custom requests, we are more than willing to entertain any creative notions you might have. Just ask.



Lumium Lighting, LLC | 3590 Cadillac Ave, Suite A, Costa Mesa, CA 92626 | Phone: 760.757.2530 | Fax: 760.283.2333 | www.lumiumlighting.com

While we always strive to ensure all website content and product information is current, Lumium Lighting reserves the right to change specifications without notice. 20220917
© Lumium Lighting, LLC - All rights reserved.



Lumium
lighting at its element

PRODUCT SPECIFICATION

- Fixture delivered light potential: 106 Lumens/Watt*
- Uniform light distribution
- 90+ CRI LED diode options
- Exceptional binning- less than 2 step MacAdams Elipse
- Minimum 70% initial lumen output at 70,000 hours
- Standard 0-10v dimming to %10
- Lutron, Eldoled, Dali, and other dimming options
- 5-year system warranty

*Actual fixture efficacy will be dependent on specification. Higher lumens per watt are achieved with lower drive powers. Please contact the factory with questions or for more information.

LUMEN OUTPUT*


DRIVER OUTPUT	LUMEN OUTPUT (PER FOOT)		LUMEN OUTPUT (PER FOOT)	
	— DIRECT —	— INDIRECT —	— DIRECT —	— INDIRECT —
VERY LOW (VLO)	4	435	4	405
LOW (LO)	6	660	6	615
STANDARD (SO)	8	865	8	805
HIGH (HO)	10	1,080	10	1,005
VERY HIGH (VHO)	12	1,260	12	1,170

DRIVER OUTPUT	LUMEN OUTPUT (PER FOOT)		LUMEN OUTPUT (PER FOOT)	
	— DIRECT —	— INDIRECT —	— DIRECT —	— INDIRECT —
VERY LOW (VLO)	16	1,740	16	1,620
LOW (LO)	24	2,640	24	2,460
STANDARD (SO)	32	3,460	32	3,220
HIGH (HO)	40	4,320	40	4,020
VERY HIGH (VHO)	48	5,040	48	4,680

- **VERY LOW:** Considerably underdrives the LEDs to maximize fixture efficacy potential and limit wattage use.
- **LOW:** Underdrives the LEDs for reasonable light output while maintaining low wattage use.
- **STANDARD:** Drives the LEDs for the best combination of lumen output and fixture efficacy.
- **HIGH:** Drive the LEDs at higher capacity for higher lumen output with good efficacy.
- **VERY HIGH:** Drives the LEDs at the highest capacity for the highest lumen output with the best efficacy.

*Lumen output will vary depending on ambient temperature. Cooler ambient and LED color temperatures result in higher luminaire performance. Calculations are based on 4000K LEDs.

LUMINOUS INTENSITY DISTRIBUTION



FIXTURE PROPERTIES (AS TESTED)

- 4' nominal length fixture
- Standard Output (SO)
- Total system energy consumption: 64 Watt
- 106 Lumens/Watt
- 4000K 80 CRI LED

ZONAL LUMEN SUMMARY

ZONE	LUMEN	%LAMP	%FIXTURE
0 - 30	770	8.9%	11.6%
0 - 40	1,271	14.7%	19.1%
0 - 60	2,350	27.2%	35.3%
0 - 90	3,450	39.9%	51.8%
90 - 120	582	6.7%	8.7%
90 - 150	2,260	26.2%	33.9%
90 - 180	3,208	37.1%	48.2%
0 - 180	6,657	77.1%	100%





REMOTE DRIVER HOUSING INFORMATION



REMOTE DRIVER HOUSING SIZES

The driver housing length is typically dictated by the options selected. Standard driver housing lengths are as shown. Non standard driver requests may increase or decrease the driver housing length. Specifications are subject to change without notice. Consult factory with questions, requests, or size limitations and we will do our best to accommodate your needs.




DRIVER HOUSING PROFILE


INSTRUCTIONS

See below for lid removal and installation instructions.

To remove the driver housing lid, use a broad slot screwdriver in the channel as shown here and twist the screwdriver ninety degrees. This may need to be done at both ends of the housing or multiple locations depending on the driver housing length.



1) Drill mounting holes in the driver housing as needed to secure to a suitable surface. (If needed, a power feed hole can be drilled into the bottom of the housing for certain mounting/power feed applications).



2) Secure the housing to the surface. (Fasteners by others)
3) Complete wire make-up.
4) Snap extruded lid onto the housing.

FINISHES

Mill Aluminum (MA) is the standard finish. Satin White and Satin Black powder coat and Satin Clear anodized finishes can be done for a small charge. Custom finishes are possible. Contact the factory for specific finish options, specific requests, RAL colors, or any other questions.



Mill Aluminum (MA)
[Standard Finish]



Satin White (SW)
[Upgrade Finish]



Satin Black (SB)
[Upgrade Finish]



Satin Clear (SC)
[Upgrade Finish]



Custom Finish (CF)
[Upgrade Finish]



NOTES

Other options are possible. Please contact the factory with custom requests.



Lumium Lighting, LLC | 3590 Cadillac Ave, Suite A, Costa Mesa, CA 92626 | Phone: 760.757.2530 | Fax: 760.283.2333 | www.lumiumlighting.com

While we always strive to ensure all website content and product information is current, Lumium Lighting reserves the right to change specifications without notice. 20220917
© Lumium Lighting, LLC - All rights reserved.



Lumium
lighting at its element

OPTIONS GUIDE

MOUNTING



CABLE SUSPENDED (CS)

Powered Suspension System. Magnesium 3 (Mg3) can be static larger down-light than up-light: Larger Aperture Direct (CSLAD), static larger up-light than down-light: Larger Aperture Indirect (CSLAI), static downlight ONLY: DIRECT (CSD), or Rotational (see below). Standard and custom power cord finishes, sleeve options, and canopy colors offer options to match almost any space. Stainless steel cables come in various lengths (4' is standard) and are field adjustable.



CABLE SUSPENDED ROTATIONAL (CS-R)

Using a similar setup to the Cable Suspended system above, the Cable Suspended- Rotational system has 360 degree rotational capacity with mechanical fasteners to lock fixtures in place if desired. This system offers incredible flexibility, light direction control, and a dynamic aesthetic.

(360 DEGREE ROTATION)



ROTATIONAL ARM MOUNT (RAM)

This system uses 5/8" diameter aluminum arms and subtle details in combination with a 360 degree rotational capacity to create some of the most versatile linear fixtures in the architectural market. Standard mounting uses 3-O mud rings (supplied by others) or a 1" optional trim ring for furniture mounted applications. Engineered with no visible fasteners, smooth rotation, and mechanical locking, the RAM system reveals an impressive aesthetic with exceptional versatility.

(360 DEGREE ROTATION)



SURFACE MOUNT (SM)

Side Mount Side (SMS). Side, the fixture is mounted on the wall giving a static bi-directional up-light and down-light.



OPTIONS GUIDE

CONTINUOUS RUN

Continuous runs are available with all fixtures and have several connection options. Single Seam continuous run options offer smooth section transitions while Component Seams lend to a more dramatic visual statement. The 360 Rotational option enables individual sections to rotate independently of each other, which offers adjustable asymmetric light distribution capacity along with striking appearances such as alternating up/down fixtures or spiral transitions. The flexibility within the rotational option makes for infinite design and functional possibilities.



CONTINUOUS RUN
SINGLE SEAM



CONTINUOUS RUN
ROTATIONAL
(SPIRAL EFFECT)



CONTINUOUS RUN
ROTATIONAL



OXYGEN 2 (O2) WITH A SINGLE SEAM CONTINUOUS RUN

CANOPIES

STANDARD

Canopies have several standard options to suit various environment aesthetics. The standard cable suspension system has 5" Satin White canopies. However, other standard options include a 2" non-power feed canopy option as well as no canopy at all. Both of these include a 5" diameter power feed canopy.

55



5" diameter power feed and 5" diameter non-pow feed canopy. Most common canopy layout. Creates a consistent ceiling aesthetic.

52



5" diameter power feed and 2" diameter non-power feed canopy. Offers a more minimal ceiling treatment while maintaining the ability to cover up mistakes. Requires a 1/4-20 stud securely fastened to the ceiling.

50



5" diameter power feed canopy and no canopy on the non-power feed side. Minimal aesthetic. Requires a 1/4-20 stud securely attached to ceiling. Works well with continuous runs where the power can be carried inside the fixture.

MACHINED

Machined canopies are 4" in diameter and can be anodized as well as powder coated to match a desired color or they can be left with a mill finish for a more striking look. Similar non-power feed options are available with this aesthetic as well. These options do carry a higher cost than standard canopies, but also have an impressive appearance.

44



4" diameter machined power feed and 4" diameter machined non-power feed canopy. Offers a consistent ceiling aesthetic with smaller machined canopies. Mill, anodized, and powder coat finishes available.

41



4" diameter machined power feed and 1-1/4" diameter machined non-power feed canopy. Offers minimal ceiling treatment while maintaining the ability to cover mistakes. Requires a 1/4-20 stud securely fastened to the ceiling. Mill, anodized, and powder coat finishes available.

40



4" diameter machined power feed canopy and no canopy on the non-power feed side. Minimal aesthetic. Requires a 1/4-20 stud securely attached to the ceiling. Works well with continuous runs where the power can be carried inside the fixture. Mill, anodized, and powder coat finishes available.

CUSTOM

Custom canopies options are available and can look spectacular in certain applications. Contact the factory with all custom requests or with any questions.



CUSTOM POWDER COAT



CUSTOM ANODIZE



CUSTOM SHAPE



Made in the USA

Lumium Lighting, LLC | 3590 Cadillac Ave, Suite A, Costa Mesa, CA 92626 | Phone: 760.757.2530 | Fax: 760.283.2333 | www.lumiumlighting.com

While we always strive to ensure all website content and product information is current, Lumium Lighting reserves the right to change specifications without notice.
© 2017 Lumium Lighting, LLC - All rights reserved.

0617




Lumium
Lighting at its element

OPTIONS GUIDE


COLOR AND FINISH

Standard finish configurations are Satin Clear (SC) housing with Machined Finish (MF) machined components (end caps, knuckles, cover plates, etc.). The incredibly clean detail within all of the machined components lends to an incredibly high end aesthetic with two tone finish. Numerous custom anodizing and powder coated finishes are available as well. If you have a particular color/finish treatment in mind, please contact the factory and we will do our best to accommodate your project needs.

STANDARD



SATIN CLEAR
ANODIZING



MACHINED
COMPONENTS

CUSTOM



MATTE BLACK



GLOSS BLACK



BRONZE



MILL ALUMINUM



SPECULAR



SATIN WHITE



GLOSS WHITE



COLOR POWDER COAT



COLOR ANODIZE



RAL COLORS

FINISHED CONFIGURATION



THALLIUM 2 (Th2)

Cable Suspended Rotational mount system with two-tone finish, Satin Clear housing and Machined Finish components.

COVER PLATES


Cover plates are standard for Rotational Arm Mounting (RAM) Systems. Standard options are Flat (FT), Curved (CV), or Trim Ring (TR). With certain applications, cover plates or trim rings may not be necessary. Contact factory with questions or for more information. Custom cover plates are also available. If a certain aesthetic is desired, please contact the factory to review any concepts and we will do our best to bring your vision to life.

STANDARD



FLAT (CPFT)

Flat has a 4" diameter cover plate for use with a 3-O mud ring.



TRIM RING (TR)

1-1/4" diameter trim ring Can be used in applications such as desk mounting.

CUSTOM



SQUARE



TALL RECTANGLE



CUSTOM

CUSTOM



Lumium Lighting, LLC | 3590 Cadillac Ave, Suite A, Costa Mesa, CA 92626 | Phone: 760.757.2530 | Fax: 760.283.2333 | www.lumiumlighting.com

While we always strive to ensure all website content and product information is current, Lumium Lighting reserves the right to change specifications without notice.

© 2017 Lumium Lighting, LLC - All rights reserved.

0617



Lumium
lighting at its element