


# Palladium 1

## CABLE SUSPENDED (CS)



### FEATURES:

- Powered Suspension System - No power cord
- High transmission frosted lenses with no diode imaging
- No visible fasteners
- Extruded aluminum housing
- Dimmable/Programmable drivers for controllable light output
- High efficacy LEDs with 5 year warranty
- Under 2 steps MacAdams Ellipse Binning
- 3/8" thick machined end caps
- Bi-directional fixture

### NOTES:

- **REQUIRES REMOTE DRIVER(S)** (see page 5 for more info)



## PRODUCT SPECIFICATION

**NOTE:** All options *italicized in gray* may increase lead times and/or incur higher costs - please consult factory with questions.

FIXTURE TYPE	MOUNTING/ ORIENTATION	NOMINAL LENGTH*	COLOR TEMP	DIRECT	LED DRIVE POWER	INDIRECT*	VOLTAGE	DRIVER	HOUSING FINISH
<div>Pd1</div>	<div></div>	<div></div>	<div></div>	<div></div>		<div></div>	<div></div>	<div></div>	<div></div>
<div>Pd1 Palladium 1</div>	<div>CS Cable Suspended - BI-DIRECTIONAL</div> <div>CSD Cable Suspended - DIRECT ONLY</div> <div>CSR Cable Suspended - ROTATIONAL</div>	<div>1' 1'-1-3/8"***</div> <div>2' 2'-1-3/8"</div> <div>3' 3'-1-3/8"***</div> <div>4' 4'-1-3/8"</div> <div>CR_Continuous Run (Specify length in nominal feet)</div> <div>*Dimensions are for reference only. Contact factory for more specific information or shop drawings. **Odd lengths may incur slightly higher per foot pricing.</div>	<div>27K 2700K</div> <div>30K 3000K</div> <div>35K 3500K</div> <div>40K 4000K</div> <div>50K 5000K</div>	<div>VLO Very Low Output 378 lumens/ft. (4w/ft.)</div> <div>LO Low Output 570 lumens/ft. (6w/ft.)</div> <div>SO Standard Output 748 lumens/ft. (8w/ft.)</div> <div>HO High Output 935 lumens/ft. (10w/ft.)</div> <div>VHO Very High Output 1,088 lumens/ft. (12w/ft.)</div> <div>CPO Custom Power Output Consult factory</div>	<div>VLO Very Low Output 378 lumens/ft. (4w/ft.)</div> <div>LO Low Output 570 lumens/ft. (6w/ft.)</div> <div>SO Standard Output 748 lumens/ft. (8w/ft.)</div> <div>HO High Output 935 lumens/ft. (10w/ft.)</div> <div>VHO Very High Output 1,088 lumens/ft. (12w/ft.)</div> <div>CPO Custom Power Output Consult factory</div> <div>*Not Applicable with CSD option. DIRECT ONLY</div>	<div>UNV Universal (120-277v)</div>	<div>ND Non-Dimming 0-10v DIMMING</div> <div>10D 10% DIM</div> <div>1D 1% DIM</div> <div>LUTRON</div> <div>LTEA Lutron Hi-Lume 1% (2-Wire)</div> <div>LDE1 Lutron EcoSystem 1% "Soft on" (Digital)</div> <div>LDES Lutron EcoSystem 5% 5-Series (Digital)</div> <div>DALI</div> <div>DALI Digital Addressable Lighting Interface</div>	<div>SC Satin Clear Anodize (Standard)</div> <div>SW Satin White (Powder Coat)</div> <div>MB Matte Black (Powder Coat)</div> <div>CF Custom Finish* (Consult factory)</div> <div>*RAL and color match are available.</div>	

HARDWARE* DETAIL FINISH	DRIVER HOUSING FINISH	CANOPY SIZE OPTIONS*	CANOPY FINISH	POWER CORD COLOR	AIRCRAFT CABLE LENGTH*	OPTIONS/ CUSTOMIZATION*
<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>
<b>MF</b> Machined Finish (Standard) <b>CF</b> Custom Finish (Consult factory)	<b>MA</b> Mill Aluminum* <b>SC</b> Satin Clear <b>SW</b> Satin White <b>SB</b> Satin Black <b>CF</b> Custom Finish (Consult factory)	5 SERIES CANOPY		<b>PSS</b> Powered Suspension System (No power cord) <b>CC</b> Custom Cord*	<b>2</b> 2' <b>4</b> 4' <b>6</b> 6' <b>8</b> 8' <b>CL</b> Custom Length Specify in feet (IE: CL10 for 10') Consult factory to confirm spec	<b>XX</b> No EMB or Customization <b>EMB7</b> 7 Watt battery back-up** (Approximately 600 lumens) <b>EMB12</b> 12 Watt battery back-up** (Approximately 1,000 lumens) <b>90</b> 90+ CRI LED BOARDS (2700K - 4000K only) <b>CD</b> Custom Driver* <b>CR</b> Customization Requested* <b>DUAL</b> Dual switching/dimming
		<b>55</b> 5" Power feed canopy 5" Non-power feed canopy	<b>SW</b> Satin White (Standard) <b>CPC</b> Custom Powder Coat canopy finish*			
		4 SERIES CANOPY				
		<b>44</b> 4" Power feed canopy 4" Non-power feed canopy	<b>MF</b> Machine Finish (Standard) <b>SW</b> Satin White <b>CF</b> Custom Finish*			
NOTE: The MF option is strongly recommended. Other options will result in higher costs and potentially longer lead times. **"Hardware" refers to the end caps and knuckles (knuckles only for the "Rotational" option).		*CONTINUOUS RUNS REQUIRE THE 55" OR THE 44" OPTION. CONSULT FACTORY WITH QUESTIONS. *See options section and installation instructions for more information.		*Just about any finish is possible. For the 4" machined canopies, MF is strongly recommended. Contact the factory with questions or requests.		*Consult factory.
*Most cost effective.						*Cables are field adjustable.
						*Consult factory for all custom options or custom concept requests. NOTE: Customization may incur higher costs and/or increased lead times. **The EMB12 is slightly more expensive than the EMB7 option (BOTH OPTIONS ARE REMOTE ONLY).

## SPECIFICATION INFORMATION

### GENERAL NOTES:

All fixtures are **UL listed** for **dry** and **damp** locations.

**REMOTE DRIVER** for all options.

Please contact the factory with any specification questions.

*Italicized grayed* out options may incur additional costs and/or extended lead times. Please consult the factory.

### FIXTURE ORIENTATION:

Bi-directional (CS) for downlight and uplight applications.

Direct (CSD) for ONLY downlight applications.

Rotational (CSR) for adjustable applications: 360 degree rotational capacity with locking mechanism.

### DRIVER: [REMOTE]

1) NON-DIMMING: As described... this fixture will not dim.

2) DIMMING: 0-10v: 1%, 10% :: Lutron: 2-wire Forward phase (Hi-Lume 1%), Ecosystem to 1% (Soft On), Ecosystem to 5% (5 Series).

"DALI" - Specify driver. See "Dimming Options" on subsequent pages for more information. For other dimming options, consult the factory.

3) EMERGENCY: Specify EMB under the Options/Customization category at the end of the cut sheet along with the desired lumen output (600 or 1,000 lumens - the latter is slightly more costly).

4) Drivers are programmed according to our standard lumen packages or to custom watt/lumen package requirements.

5) Consult factory with any questions or specification requirements.

### FINISHES:

The standard finish is a Satin Clear anodized housing with Machine Finished hardware. Machined finish is preferable for machined components (Hardware Detail) - Powder coating these parts may result in additional costs. Consult the factory with any questions about standard or custom finishing options.


### CUSTOMIZATION:

We have numerous custom options available. However, if there is something unique required for a project, from simple options to complete custom requests, we are more than willing to entertain any creative notions you might have. Just ask.



# Palladium 1

## ROTATIONAL ARM MOUNT (RAM)




### FEATURES:

- 5/8" diameter rigid tube mounting system
- High transmission frosted lenses with no diode imaging
- No visible fasteners
- Extruded aluminum housing
- Dimmable/Programmable drivers for controllable light output
- High efficacy LEDs with 5 year warranty
- Under 2 steps MacAdams Ellipse Binning
- 3/8" thick machined end caps
- Bi-directional fixture
- 360° rotation option- with mechanical locking

### NOTES:

- **REQUIRES REMOTE DRIVER(S)** (see page 5 for more info)



## PRODUCT SPECIFICATION

**NOTE:** All options *italicized in gray* may increase lead times and/or incur higher costs - please consult factory with questions.

FIXTURE TYPE	MOUNTING	NOMINAL LENGTH*	COLOR TEMP	DIRECT	LED DRIVE POWER	INDIRECT	VOLTAGE	DRIVER	HOUSING FINISH
<div>Pd1</div>	<div>RAM</div>	<div></div>	<div></div>	<div></div>		<div></div>	<div></div>	<div></div>	<div></div>
<b>Pd1</b> Palladium 1	<b>RAM</b> Rotational Arm Mount	<div>1' 1'-3/8"***</div> <div>2' 2'-1-3/8"***</div> <div>3' 3'-1-3/8"***</div> <div>4' 4'-1-3/8"***</div> <div>CR_ ' Continuous Run (Specify length in nominal feet)</div> <div>*Dimensions are for reference only. Contact factory for more specific information or shop drawings.</div> <div>**Odd lengths may incur slightly higher per foot pricing.</div>	<div>27K 2700K</div> <div>30K 3000K</div> <div>35K 3500K</div> <div>40K 4000K</div> <div>50K 5000K</div>	<div>VLO Very Low Output 378 lumens/ft. (4w/ft.)</div> <div>LO Low Output 570 lumens/ft. (6w/ft.)</div> <div>SO Standard Output 748 lumens/ft. (8w/ft.)</div> <div>HO High Output 935 lumens/ft. (10w/ft.)</div> <div>VHO Very High Output 1,088 lumens/ft. (12w/ft.)</div> <div>CPO Custom Power Output Consult factory</div>	<div>VLO Very Low Output 378 lumens/ft. (4w/ft.)</div> <div>LO Low Output 570 lumens/ft. (6w/ft.)</div> <div>SO Standard Output 748 lumens/ft. (8w/ft.)</div> <div>HO High Output 935 lumens/ft. (10w/ft.)</div> <div>VHO Very High Output 1,088 lumens/ft. (12w/ft.)</div> <div>CPO Custom Power Output Consult factory</div>	<b>UNV</b> Universal (120-277v)	<div>ND Non-Dimming 0-10v DIMMING</div> <div>10D 10% DIM</div> <div>1D 1% DIM</div> <div>LUTRON</div> <div>LTEA Lutron Hi-Lume 1% (2-Wire)</div> <div>LDE1 Lutron EcoSystem 1% "Soft on" (Digital)</div> <div>LDES Lutron EcoSystem 5% 5-Series (Digital)</div> <div>DALI</div> <div>DALI Digital Addressable Lighting Interface</div>	<div>SC Satin Clear Anodize (Standard)</div> <div>SW Satin White (Powder Coat)</div> <div>MB Matte Black (Powder Coat)</div> <div>CF Custom Finish* (Consult factory)</div> <div>*RAL and color match are available.</div>	

\*Dimensions are for reference only. Contact factory for more specific information or shop drawings.  
\*\*Odd lengths may incur slightly higher per foot pricing.

\*RAL and color match are available.


HARDWARE* DETAIL FINISH	DRIVER HOUSING FINISH	ARM LENGTH*	MOUNTING/ COVER PLATE	OPTIONS/ CUSTOMIZATION
<b>MF</b> Machined Finish (Standard) <b>CF</b> Custom Finish (Consult factory)	<b>MA</b> Mill Aluminum* <b>SC</b> Satin Clear <b>SW</b> Satin White <b>SB</b> Satin Black <b>CF</b> Custom Finish (Consult factory)	<b>3</b> 3" <b>6</b> 6" <b>9</b> 9"*** <b>12</b> 12"*** <b>CAL</b> Custom Arm Length-Consult factory	<b>4CPF</b> Flat 4" diameter Cover Plate - For use with a 3-O mud ring <b>CCP</b> Custom Cover Plate (Consult factory)	<b>XX</b> No EMB or Customization <b>EMB7</b> 7 Watt battery back-up** (Approximately 600 lumens) <b>EMB12</b> 12 Watt battery back-up** (Approximately 1,000 lumens) <b>90</b> (2700K - 4000K only) Corners/patterns* <b>CD</b> Custom Driver* <b>CR</b> Customization Requested* <b>DUAL</b> Dual switching/dimming

**NOTE:** The MF option is strongly recommended. Other options will result in higher costs and potentially longer lead times.  
\*\*"Hardware" refers to the end caps, knuckles, arms, and cover plates.

\*Most cost effective.

\*Arm length is measured from the mounting surface to the center of the fixture.  
\*\*Limitations apply. Consult factory.

\*Consult factory for all custom options or custom concept requests.  
**NOTE:** Customization may incur higher costs and/or increased lead times.  
\*\*The EMB12 is slightly more expensive than the EMB7 option (BOTH OPTIONS ARE REMOTE ONLY).



ROTATIONAL ARM MOUNT INFORMATION

## SPECIFICATION INFORMATION

### GENERAL NOTES:

All fixtures are **UL listed** for **dry** and **damp** locations.

**REMOTE DRIVER** for all options.

Please contact the factory with any specification questions.

*Italicized grayed* out options may incur additional costs and/or extended lead times. Please consult the factory.

### DRIVER: [REMOTE]

- 1) NON-DIMMING: As described... this fixture will not dim.
- 2) DIMMING: 0-10v: 1%, 10% :: Lutron: 2-wire Forward phase (Hi-Lume 1%), Ecosystem to 1% (Soft On), Ecosystem to 5% (5 Series). "DALI" - Specify driver. See "Dimming Options" on subsequent pages for more information. For other dimming options, consult the factory.
- 3) EMERGENCY: Specify EMB under the Options/Customization category at the end of the cut sheet along with the desired lumen output (600 or 1,000 lumens - the latter is slightly more costly).
- 4) Drivers are programmed according to our standard lumen packages or to custom watt/lumen package requirements.
- 5) Consult factory with any questions or specification requirements.

### FINISHES:

The standard finish is a Satin Clear anodized housing with Machine Finished hardware. Machined finish is preferable for machined components (Hardware Detail) - Powder coating these parts may result in additional costs. Consult the factory with any questions about standard or custom finishing options.


### CUSTOMIZATION:

We have numerous custom options available. However, if there is something unique required for a project, from simple options to complete custom requests, we are more than willing to entertain any creative notions you might have. Just ask.



# Palladium 1

## SURFACE MOUNT (SM)



### FEATURES:

- Ceiling or wall mounting system
- High transmission frosted lenses with no diode imaging
- No visible fasteners
- Extruded aluminum housing
- Dimmable/Programmable drivers for controllable light output
- High efficacy LEDs with 5 year warranty
- Under 2 steps MacAdams Ellipse Binning
- 3/8" thick machined end caps
- Bi-directional fixture

### NOTES:

- **REQUIRES REMOTE DRIVER(S)** (see page 5 for more info)



## PRODUCT SPECIFICATION

**NOTE:** All options *italicized in gray* may increase lead times and/or incur higher costs - please consult factory with questions.

FIXTURE TYPE	MOUNTING/ ORIENTATION	NOMINAL LENGTH*	COLOR TEMP	DIRECT	LED DRIVE POWER	INDIRECT*	VOLTAGE	DRIVER	HOUSING FINISH
<b>Pd1</b>									
<b>Pd1</b> Palladium 1	<b>SMS</b> Surface Mount - SIDE <b>SMSD</b> Surface Mount - SIDE DIRECT ONLY	1' 1'-1-3/8"*** 2' 2'-1-3/8"*** 3' 3'-1-3/8"*** 4' 4'-1-3/8"*** <b>CR</b> Continuous Run (Specify length in nominal feet)	27K 2700K 30K 3000K 35K 3500K 40K 4000K 50K 5000K	<b>VLO</b> Very Low Output 378 lumens/ft. (4w/ft.) <b>LO</b> Low Output 570 lumens/ft. (6w/ft.) <b>SO</b> Standard Output 748 lumens/ft. (8w/ft.) <b>HO</b> High Output 935 lumens/ft. (10w/ft.) <b>VHO</b> Very High Output 1,088 lumens/ft. (12w/ft.) <b>CPO</b> Custom Power Output Consult factory	<b>VLO</b> Very Low Output 378 lumens/ft. (4w/ft.) <b>LO</b> Low Output 570 lumens/ft. (6w/ft.) <b>SO</b> Standard Output 748 lumens/ft. (8w/ft.) <b>HO</b> High Output 935 lumens/ft. (10w/ft.) <b>VHO</b> Very High Output 1,088 lumens/ft. (12w/ft.) <b>CPO</b> Custom Power Output Consult factory		<b>UNV</b> Universal (120-277v)	<b>ND</b> Non-Dimming 0-10v DIMMING <b>10D</b> 10% DIM <b>1D</b> 1% DIM LUTRON <b>LTEA</b> Lutron Hi-Lume 1% (2-Wire) <b>LDE1</b> Lutron EcoSystem 1% "Soft on" (Digital) <b>LDES</b> Lutron EcoSystem 5% 5-Series (Digital) DALI <b>DALI</b> Digital Addressable Lighting Interface	<b>SC</b> Satin Clear Anodize (Standard) <b>SW</b> Satin White (Powder Coat) <b>MB</b> Matte Black (Powder Coat) <b>CF</b> Custom Finish* (Consult factory)

\*Dimensions are for reference only. Contact factory for more specific information or shop drawings.  
\*\*Odd lengths may incur slightly higher per foot pricing.

\*Not Applicable with SMSD option. DIRECT ONLY.

\*RAL and color match are available.

HARDWARE* DETAIL FINISH	DRIVER HOUSING FINISH	STAND OFF DISTANCE	OPTIONS/ CUSTOMIZATION*
<b>MF</b> Machined Finish (Standard) <b>CF</b> Custom Finish (Consult factory)	<b>MA</b> Mill Aluminum* <b>SC</b> Satin Clear <b>SW</b> Satin White <b>SB</b> Satin Black <b>CF</b> Custom Finish (Consult factory)	<b>0</b> Flush <b>.5</b> Half inch <b>1</b> 1" <b>3</b> 3" <b>6</b> 6" <b>CU</b> Custom - Specify in inches (IE: CU4.5)	<b>XX</b> No EMB or Customization <b>EMB7</b> 7 Watt battery back-up** (Approximately 600 lumens) <b>EMB12</b> 12 Watt battery back-up** (Approximately 1,000 lumens) <b>90</b> 90+ CRI LED BOARDS (2700K - 4000K only) <b>CD</b> Custom Driver* <b>CR</b> Customization Requested* <b>DUAL</b> Dual switching/dimming

NOTE: The MF option is strongly recommended. Other options will result in higher costs and potentially longer lead times.  
\*\*"Hardware" refers to the end caps and knuckles (knuckles only for the "Rotational" option).

\*Most cost effective.

\*Consult factory for all custom options or custom concept requests.  
NOTE: Customization may incur higher costs and/or increased lead times.  
\*\*The EMB12 is slightly more expensive than the EMB7 option (BOTH OPTIONS ARE REMOTE ONLY).

## SPECIFICATION INFORMATION

### GENERAL NOTES:

All fixtures are **UL listed** for **dry** and **damp** locations.

**REMOTE DRIVER** for all options.

Please contact the factory with any specification questions.

*Italicized grayed* out options may incur additional costs and/or extended lead times. Please consult the factory.

### DRIVER: [REMOTE]

- 1) NON-DIMMING: As described... this fixture will not dim.
- 2) DIMMING: 0-10v: 1%, 10% :: Lutron: 2-wire Forward phase (Hi-Lume 1%), Ecosystem to 1% (Soft On), Ecosystem to 5% (5 Series). "DALI" - Specify driver. See "Dimming Options" on subsequent pages for more information. For other dimming options, consult the factory.
- 3) EMERGENCY: Specify EMB under the Options/Customization category at the end of the cut sheet along with the desired lumen output (600 or 1,000 lumens - the latter is slightly more costly).
- 4) Drivers are programmed according to our standard lumen packages or to custom watt/lumen package requirements.
- 5) Consult factory with any questions or specification requirements.

### FINISHES:

The standard finish is a Satin Clear anodized housing with Machine Finished hardware. Machined finish is preferable for machined components (Hardware Detail) - Powder coating these parts may result in additional costs. Consult the factory with any questions about standard or custom finishing options.

### CUSTOMIZATION:

We have numerous custom options available. However, if there is something unique required for a project, from simple options to complete custom requests, we are more than willing to entertain any creative notions you might have. Just ask.



## LED COMPONENT INFORMATION

- Fixture delivered light potential: 95 Lumens/Watt\*
- Uniform light distribution
- 90+ CRI LED diode options
- Exceptional binning- less than 2 step MacAdams Ellipse
- Minimum 70% initial lumen output at 70,000 hours
- Standard 0-10v dimming to %10
- Lutron, Eldoled, Dali, and other dimming options
- 5 year system warranty

\*Actual fixture efficacy will be dependent on specification. Higher lumens per watt are achieved with lower drive powers. Please contact the factory with questions or for more information.

## LUMEN OUTPUT \*


DRIVER OUTPUT	LUMEN OUTPUT (PER FOOT)	
	WATTAGE	LUMENS
VERY LOW (VLO)	8	756
LOW (LO)	12	1,140
STANDARD (SO)	16	1,496
HIGH (HO)	20	1,870
VERY HIGH (VHO)	24	2,176

DRIVER OUTPUT	PER 4' FIXTURE (TOTAL DELIVERED LUMENS)	
	WATTAGE	LUMENS
VERY LOW (VLO)	32	3,024
LOW (LO)	48	4,560
STANDARD (SO)	64	5,984
HIGH (HO)	80	7,480
VERY HIGH (VHO)	96	8,704

- **VERY LOW:** Considerably underdrives the LEDs to maximize fixture efficacy potential and limit wattage use.
- **LOW:** Underdrives the LEDs for reasonable light output while maintaining low wattage use.
- **STANDARD:** Drives the LEDs for the best combination of lumen output and fixture efficacy.
- **HIGH:** Drive the LEDs at higher capacity for higher lumen output with good efficacy.
- **VERY HIGH:** Drives the LEDs at the highest capacity for the highest lumen output with the best efficacy.

\*Lumen output will vary depending on ambient temperature. Cooler ambient and LED color temperatures result in higher luminaire performance. Calculations are based on 3500K LEDs.

## LUMINOUS INTENSITY DISTRIBUTION





## FIXTURE PROPERTIES (AS TESTED)

- 4' nominal length fixture
- Standard Output (SO)
- Total system energy consumption: 64 Watt
- 95 Lumens/Watt
- 4000K 80 CRI LED

## ZONAL LUMEN SUMMARY




ZONE	LUMEN	%LAMP	%FIXTURE
0 - 30	703	8.1%	12.1%
0 - 40	1,154	13.4%	19.9%
0 - 60	2,108	24.4%	36.4%
0 - 90	2,987	34.6%	51.6%
90 - 120	881	10.2%	15.2%
90 - 150	2,285	26.5%	39.5%
90 - 180	2,986	34.6%	51.6%
0 - 180	5,974	69.2%	103.2%



# REMOTE DRIVER HOUSING INFORMATION

## REMOTE DRIVER HOUSING SIZES


The driver housing length is typically dictated by the options selected. Standard driver housing lengths are as shown. Non standard driver requests may increase or decrease the driver housing length. Specifications are subject to change without notice. Consult factory with questions, requests, or size limitations and we will do our best to accommodate your needs.




## INSTRUCTIONS

See below for lid removal and installation instructions.

To remove the driver housing lid, use a broad slot screwdriver in the channel as shown here and twist the screwdriver ninety degrees. This may need to be done at both ends of the housing or multiple locations depending on the driver housing length.



1) Drill mounting holes in the driver housing as needed to secure to a suitable surface. (If needed, a power feed hole can be drilled into the bottom of the housing for certain mounting/power feed applications).




2) Secure the housing to the surface.  
(Fasteners by others)  
3) Complete wire make-up.  
4) Snap extruded lid onto the housing.

## FINISHES

Mill Aluminum (MA) is the standard finish. Satin White and Satin Black powder coat and Satin Clear anodized finishes can be done for a small charge. Custom finishes are possible. Contact the factory for specific finish options, specific requests, RAL colors, or any other questions.



Mill Aluminum (MA)  
[Standard finish]



Satin White (SW)  
[Upgrade finish]



Satin Black (SB)  
[Upgrade finish]



Satin Clear (SC)  
[Upgrade finish]



Custom Finish (CF)  
[Custom finish]



## NOTES

Other options are possible. Please contact the factory with custom requests.

Lumium Lighting, LLC | 3590 Cadillac Ave, Suite A, Costa Mesa, CA 92626 | Phone: 760.757.2530 | Fax: 760.283.2333 | [www.lumiumlighting.com](http://www.lumiumlighting.com)

While we always strive to ensure all website content and product information is current, Lumium Lighting reserves the right to change specifications without notice.  
© 2017 Lumium Lighting, LLC - All rights reserved.

0617




**Lumium**  
lighting at its element




# OPTIONS GUIDE

## MOUNTING



### CABLE SUSPENDED (CS)



Powered Suspension System. Palladium 1 (Pd1) can be static down-light and up-light: Bi-Directional (CS), static down-light ONLY: Direct (CSD), or Rotational (see below). Standard and custom power cord finishes, sleeve options, and canopy colors offer options to match almost any space. Stainless steel cables come in various lengths (4' is standard) and are field adjustable.



### CABLE SUSPENDED ROTATIONAL (CS-R)

Using a similar setup to the Cable Suspended system above, the Cable Suspended- Rotational system has 360 degree rotational capacity with mechanical fasteners to lock fixtures in place if desired. This system offers incredible flexibility, light direction control, and a dynamic aesthetic.

(360 DEGREE ROTATION)



### ROTATIONAL ARM MOUNT (RAM)

This system uses 5/8" diameter aluminum arms and subtle details in combination with a 360 degree rotational capacity to create some of the most versatile linear fixtures in the architectural market. Standard mounting uses 3-O mud rings (supplied by others) or a 1" optional trim ring for furniture mounted applications. Engineered with no visible fasteners, smooth rotation, and mechanical locking, the RAM system reveals an impressive aesthetic with exceptional versatility.

(360 DEGREE ROTATION)



### SURFACE MOUNT (SM)

Side Mount Side (SMS) or Side Mount Direct Only (SMSD). Side, the fixture is mounted on the wall giving a static bi-directional up-light and down-light. Direct Only, the fixture is mounted on the wall as well but only gives a static down-light.



# OPTIONS GUIDE

## CONTINUOUS RUN

Continuous runs are available with all fixtures and have several connection options. Single Seam continuous run options offer smooth section transitions while Component Seams lend to a more dramatic visual statement. The 360 Rotational option enables individual sections to rotate independently of each other, which offers adjustable asymmetric light distribution capacity along with striking appearances such as alternating up/down fixtures or spiral transitions. The flexibility within the rotational option makes for infinite design and functional possibilities.




CONTINUOUS RUN  
SINGLE SEAM



CONTINUOUS RUN  
ROTATIONAL  
(SPIRAL EFFECT)



CONTINUOUS RUN  
ROTATIONAL



OXYGEN 2 (O2) WITH A SINGLE SEAM CONTINUOUS RUN

## CANOPIES

### STANDARD

Canopies have several standard options to suit various environment aesthetics. The standard cable suspension system has 5" Satin White canopies. However, other standard options include a 2" non-power feed canopy option as well as no canopy at all. Both of these include a 5" diameter power feed canopy.

55



5" diameter power feed and 5" diameter non-pow feed canopy. Most common canopy layout. Creates a consistent ceiling aesthetic.

52



5" diameter power feed and 2" diameter non-power feed canopy. Offers a more minimal ceiling treatment while maintaining the ability to cover up mistakes. Requires a 1/4-20 stud securely fastened to the ceiling.

50



5" diameter power feed canopy and no canopy on the non-power feed side. Minimal aesthetic. Requires a 1/4-20 stud securely attached to ceiling. Works well with continuous runs where the power can be carried inside the fixture.

### MACHINED

Machined canopies are 4" in diameter and can be anodized as well as powder coated to match a desired color or they can be left with a mill finish for a more striking look. Similar non-power feed options are available with this aesthetic as well. These options do carry a higher cost than standard canopies, but also have an impressive appearance.

44



4" diameter machined power feed and 4" diameter machined non-power feed canopy. Offers a consistent ceiling aesthetic with smaller machined canopies. Mill, anodized, and powder coat finishes available.

41



4" diameter machined power feed and 1-1/4" diameter machined non-power feed canopy. Offers minimal ceiling treatment while maintaining the ability to cover mistakes. Requires a 1/4-20 stud securely fastened to the ceiling. Mill, anodized, and powder coat finishes available.

40




4" diameter machined power feed canopy and no canopy on the non-power feed side. Minimal aesthetic. Requires a 1/4-20 stud securely attached to the ceiling. Works well with continuous runs where the power can be carried inside the fixture. Mill, anodized, and powder coat finishes available.

### CUSTOM

Custom canopy options are available and can look spectacular in certain applications. Contact the factory with all custom requests or with any questions.



CUSTOM POWDER COAT



CUSTOM ANODIZE



CUSTOM SHAPE




# OPTIONS GUIDE


## COLOR AND FINISH

Standard finish configurations are Satin Clear (SC) housing with Machined Finish (MF) machined components (end caps, knuckles, cover plates, etc.). The incredibly clean detail within all of the machined components lends to an incredibly high end aesthetic with two tone finish. Numerous custom anodizing and powder coated finishes are available as well. If you have a particular color/finish treatment in mind, please contact the factory and we will do our best to accommodate your project needs.

### STANDARD



SATIN CLEAR  
ANODIZING



MACHINED  
COMPONENTS

### CUSTOM



MATTE BLACK



GLOSS BLACK



BRONZE



MILL ALUMINUM



SPECULAR



SATIN WHITE



GLOSS WHITE



COLOR POWDER COAT



COLOR ANODIZE



RAL COLORS

### FINISHED CONFIGURATION



THALLIUM 2 (Th2)

Cable Suspended Rotational mount system with two-tone finish, Satin Clear housing and Machined Finish components.

## COVER PLATES


Cover plates are standard for Rotational Arm Mounting (RAM) Systems. Standard options are Flat (FT), Curved (CV), or Trim Ring (TR). With certain applications, cover plates or trim rings may not be necessary. Contact factory with questions or for more information. Custom cover plates are also available. If a certain aesthetic is desired, please contact the factory to review any concepts and we will do our best to bring your vision to life.

### STANDARD



FLAT (CPFT)


Flat has a 4" diameter cover plate for use with a 3-O mud ring.



TRIM RING (TR)

1-1/4" diameter trim ring Can be used in applications such as desk mounting.

### CUSTOM



SQUARE



TALL RECTANGLE



CUSTOM

CUSTOM

