OVERVIEW • SPECIFICATIONS DIMMER COMPATIBILITY | TROV FLEX DRIVERS FIRM DATE PROJECT TYPE

### NORTH AMERICAN SINGLE OUTPUT DRIVERS

	Dimmer			-E-96W 77-SBC	DRV-M- 120/27			-E-40W 77-SBC	DRV-E10			0-E-60W 77-LTF		0-E-40W 277-LTF
		Voltage	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
TRIAC	/MLV													
Lutron	Skylark Contour CTCL-153P Skylark Contour CT-600P Diva DV-600P Skylark SCL-153P Skylark 600P Caseta Wireless PD-6WCL Ariadni MLV AYLV-600P	120VAC 120VAC 120VAC 120VAC 120VAC 120VAC 120VAC	99.6% 99.6% 99.6% 99.9% 99.8% 99.8%	0.0% 0.0% 0.0% 0.0% 0.0% 0.0%	99.6% 99.5% 99.8% 99.7% 99.8% 99.8%	0.0% 0.0% 0.0% 0.0% 0.0% 0.0%	99.4% 99.3% 99.4% 99.9% 99.9% 99.9%	0.0% 0.0% 0.0% 0.0% 0.0% 0.0%	94.2% 97.8% 100.0% 99.6% 98.7% 97.8% 97.8%	1.9% 0.0% 0.0% 2.2% 0.0% 2.2% 0.0%	99.8% 100.0% 99.8% 99.9% 99.5% 99.7% 99.9%	11.7% 5.9% 1.1% 2.5% 4.6% 58.4% 32.1%	99.8% 99.5% 99.9% 99.9% 99.2% 99.5% 99.2%	17.6% 2.6% 1.9% 5.3% 7.9% 42.2% 23.2%
Leviton	Illumatech IPI10 Sure Slide 6672-L DSM10 MLV Illumatech IPL06 Sure Slide 6674	120VAC 120VAC 120VAC 120VAC 120VAC	99.8% 99.8% 99.7% 99.8% 99.9%	0.0% 0.0% 0.0% 0.0%	99.7% 99.8% 99.7% 99.8% 99.9%	0.0% 0.0% 0.0% 0.0% 0.0%	99.8% 99.9% 99.9% 99.9% 99.9%	0.0% 0.0% 0.0% 0.0%	100.0% 99.1% NG COMPA		99.9% 99.6% 100.0% 99.7% 99.3%	20.7% 22.7% 39.3% 49.2% 86.3%	99.7% 99.3% NOT CON 99.5% 99.5%	29.1% 28.8% <b>IPATIBLE</b> 58.8% 59.9%
Eaton	SIOGP SIIOP DALOGP	120VAC 120VAC 120VAC	99.6% 99.6% 99.8%	0.0% 0.0% 0.0%	99.7% 99.5% 99.5%	0.0% 0.0% 0.0%	99.9% 99.9% 99.9%	0.0% 0.0% 0.0%	100.0% 100.0% 100.0%	0.0% 0.0% 0.0%	99.6% 99.5% 99.6%	28.3% 26.2% 19.6%	99.7% <b>NOT COM</b> 98.9%	

## **ELV**

Lutuan	Skylark ELV SELV-300P	120VAC	NOT	100.0%	0.0%	100.0%	38.1%	99.5%	27.4%
Lutron	Skylark Contour ELV CTELV-303P	120VAC	COMPATIBLE	100.0%	0.0%	100.0%	35.4%	99.2%	25.4%

### 0-10V

Lutron	Diva DVSTV	120VAC		100.0%	6.8%	100.0%	0%	100%	0%
Eaton	SF10P	120VAC	NOT COMPATIBLE	100.0%	7.6%	100.0%	0%	100%	0%
Leviton	IP710-DL	120VAC		94.0%	0%	100.0%	0.2%	99%	0%

FREEDOM TO CREATE™



OVERVIEV	W • SPECIFICATION	S				DIMME	ER COMF	PATIBILITY	TROV FLEX DRIVER
DATE	PROJECT				FIRM				TYPE
NORTH	I AMERICAN M	1ULTI-OL	JTPUT DR	IVERS					
	Dimmer	Input Voltage	DRV-E10-E-96	DIVELIO	-E-96WX3- 77-KVG	DRV-E10-1	E-96WX4- '7-KVG		
			MAX M	IIN MAX	MIN	MAX	MIN		
TRIAC/	MLV								
Lutron -	Skylark Contour CTCL-153P	120VAC	99.9% 2	2.0% 99.2%	2.0%	99.9%	2.0%		
Lutron	Skylark 600P	120VAC	99.9%	1.0% 99.0%	1.0%	99.0%	1.0%		
ELV									
Lutron	Skylark Contour ELV CTELV-303P	120VAC	98.8% 1	1.0% 98.8%	1.0%	98.8%	1.0%		
0-10V									

Lutron

855.6.ECOSEN

120VAC

Diva DVSTV

100%

1.0%

100%

1.0%

100%

1.0%



OVERVIEW • SF	PECIFICATIONS	DIMMER COMPATIBILITY   TROV F	LEX DRIVERS
DATE	PROJECT	FIRM	TYPE

### INTERNATIONAL DRIVERS

	<u> </u>	DRV-E10-E-120W	DRV-E10-E-100W-	DRV-DALI-E-120W-	DRV-DALI-E-100W-
Dimmer	Input Voltage	90-305-PWM	100-305-ELG	90-305-PWM	100-305-ELG
		MAX MIN	MAX MIN	MAX MIN	MAX MIN

# 0-10V

Lutron	Diva DVSTV Homeworks QS QSNE-4T10-D	230V 230V	100.0%	4.7% 0.9%	100.0% 19.8% Not Tested	
Eaton	SF10P	230V	100.0%	11.3%	100.0% 22.3%	NOT COMPATIBLE
Leviton	IP710-DL	230V	86.5%	1.7%	100.0% 16.5%	
Casambi	CBU-A2D	230V	100.0%	9.9%	Not Tested	

### DALI

Generic	Generic DALI Control	230V	NOT COMPATIBLE	100.0%   0.2%	100.0%   11.8%	

<sup>\*</sup>Minimum and Maximum percentages are calculated by measuring light output when the dimmer is set to full bright for max, and to the lowest stable output level for min. Those measurements are then divided by the light output measured when no dimmer is installed.

FREEDOM TO CREATE™